Safety Data Sheet ULTRABOND ECO 380

Safety Data Sheet dated: 22/12/2023 - version 5



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: ULTRABOND ECO 380

Trade code: 9019434

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Water-borne synthetic polymer based adhesive

Uses advised against: Not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960 - www.mapei.co.uk (office hour 8:30-17:30)

Responsable: sicurezza@mapei.it

1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)333 333 9962

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Special Provisions:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -

isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: No other hazards

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not Relevant

3.2. Mixtures

Mixture identification: ULTRABOND ECO 380

Hazardous components within the meaning of the CLP regulation and related classification:

Qty Name Ident. Numb. Classification Registration Number ≥ 1 - <2.5 1-Phenoxypropan-2-ol CAS:770-35-4 Eye Irrit. 2, H319 01-2119486566-23-XXXX EC:212-222-7

Print date 22/12/2023 Production Name ULTRABOND ECO 380 Page n. 1 of 9

1,2-benzisothiazol-3(2H)-one; 1,2-CAS:2634-33-5 ≥0.01 -<0.016 % benzisothiazolin-3-one

EC:220-120-9 Index:613-088-00-6

Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Acute Tox. 4, H302 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Specific Concentration Limits: C ≥ 0.05%: Skin Sens. 1 H317

<0.0015 % reaction mass of: 5-chloro-2methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - Index:613-167isothiazol-3-one [EC no. 220-239- 00-5 6] (3:1)

EC:611-341-5

CAS:55965-84-9 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 3, H301 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Acute Tox. 2, H310 Acute Tox. 2, H330 Eye Dam. 1, H318, M-Chronic: 100, M-Acute: 100, EUH071

> Specific Concentration Limits: C ≥ 0.6%: Skin Corr. 1C H314 $0.06\% \le C < 0.6\%$: Skin Irrit. 2 H315 C ≥ 0.6%: Eye Dam. 1 H318 $0.06\% \le C < 0.6\%$: Eye Irrit. 2

C ≥ 0.0015%: Skin Sens. 1A H317

H319

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

Not available (see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Print date 22/12/2023 Production Name **ULTRABOND ECO 380** 2 of 9 Page n.

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Predicted No Effect Concentration (PNEC) values

1-Phenoxypropan-2-ol

Exposure Route: Fresh Water; PNEC Limit: 0.1 mg/l

CAS: 770-35-4

Exposure Route: Marine water; PNEC Limit: 0.01 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0.38 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 0.038 mg/kg

Derived No Effect Level (DNEL) values

1-Phenoxypropan-2-ol CAS: 770-35-4

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Worker Industry: 42 mg/kg; Consumer: 21 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Industry: 25.7 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 3.65 mg/kg

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user

Print date 22/12/2023 Production Name ULTRABOND ECO 380 Page n. 3 of 9

information.

Not needed for normal use. Anyway, operate according good working practices.

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Appearance: paste Color: Cream

Odour: Characteristic

Odour threshold: Not available

Melting point / freezing point: 0 °C (32 °F)

Initial boiling point and boiling range: 100 °C (212 °F)

Flammability: N.A.

Lower and upper explosion limit: Not available

Flash point: Not available

Auto-ignition temperature: Not available Decomposition temperature: Not available

pH: 9.00

pH (water dispersion, 10%): 8.50

Viscosity: 85,000.00 cPs

Kinematic viscosity: > 20,5 mm2/sec (40 °C) mm2/s

Solubility in water: dispersible Solubility in oil: insoluble

Partition coefficient (n-octanol/water): Not available

Vapour pressure: 2.34
Relative density: 1.25 g/cm3
Vapour density: 0.017
Particle characteristics:
Particle size: Not available

9.2. Other information

Miscibility: Not available Conductivity: Not available Explosive properties: == No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

Print date 22/12/2023 Production Name ULTRABOND ECO 380 Page n. 4 of 9

c) serious eye damage/irritation Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

1-Phenoxypropan-2-ol a) acute toxicity LD50 Skin Rabbit > 2000 mg/kg

LC50 Inhalation Rat > 5400 mg/m3 4h

1,2-benzisothiazol-3(2H)- a) acute toxicity

one; 1,2-benzisothiazolin-

3-one

LD50 Oral Rat = 670 mg/kg

reaction mass of: 5- a) acute toxicity

chloro-2-methyl-4isothiazolin-3-one [EC no. 247-500-7] and 2methyl-2H -isothiazol-3one [EC no. 220-239-6]

(3:1)

LC50 Inhalation Rat = 2.36 mg/l 4h

LD50 Skin Rabbit = 660 mg/kg LD50 Oral Rat = 53 mg/kg

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

List of Eco-Toxicological properties of the components

Component Ident. Numb. Ecotox Data

1-Phenoxypropan-2-ol CAS: 770-35-4 - a) Aquatic acute toxicity : LC50 Fish > 100 mg/L 96h

EINECS: 212-

222-7

a) Aquatic acute toxicity : LC50 Daphnia = 370 mg/L 48h a) Aquatic acute toxicity : EC50 Algae > 100 mg/L 72h

1,2-benzisothiazol-3(2H)-one; 1,2- CAS: 2634-33-5 a) Aquatic acute toxicity: LC50 Fish = 2.15 mg/L

benzisothiazolin-3-one - EINECS: 220-

120-9 - INDEX: 613-088-00-6

b) Aquatic chronic toxicity: NOEC Algae = 0.0403 mg/L 72h

Print date 22/12/2023 Production Name ULTRABOND ECO 380 Page n. 5 of 9

b) Aquatic chronic toxicity: EC50 Algae = 0.11 mg/L 72h

b) Aquatic chronic toxicity: EC10 Algae = 0.04 mg/L 72h

b) Aquatic chronic toxicity: EC50 Daphnia = 3.27 mg/L 48h

NOEC Daphnia = 1.2 mg/L 21d

reaction mass of: 5-chloro-2methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - 611-341-5 isothiazol-3-one [EC no. 220-239-6] (3:1) INDEX: 613-167-00-5

CAS: 55965-84- a) Aquatic acute toxicity: EC50 Daphnia = 0.12 mg/L 48

a) Aquatic acute toxicity : LC50 Fish = 0.22 mg/L 96

a) Aquatic acute toxicity: EC50 Algae = 0.048 mg/L 72

b) Aquatic chronic toxicity: NOEC Algae = 0.0012 mg/L 72

b) Aquatic chronic toxicity : NOEC Fish = 0.098 mg/L - 28 db) Aquatic chronic toxicity : NOEC Daphnia = 0.004 mg/L - 21 d

12.2. Persistence and degradability

NΑ

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

ΝΔ

12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

Not available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Clean waste packaging should be recycled when possible and authorized by the authority.

Hazardous waste: No

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

Not Applicable

14.2. UN proper shipping name

Not Applicable

14.3. Transport hazard class(es)

Print date 22/12/2023 Production Name ULTRABOND ECO 380 Page n. 6 of 9

Not Applicable

14.4. Packing group

Not Applicable

14.5. Environmental hazards

Not Applicable

14.6. Special precautions for user

Not Applicable

Road and Rail (ADR-RID):

Not Applicable

Air (IATA):

Not Applicable

Sea (IMDG):

Not Applicable

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC): N.A. g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP) Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP) Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

None

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: None.

Restrictions related to the substances contained: 28, 30, 72, 75

SVHC Substances:

SVHC substances not present in a concentration $\geq 0.1\%$ (w/w)

German Water Hazard Class.

Class 1: slightly hazardous for water.

Regulation (UE) 2019/1148 (Explosive precursors): No substances contained

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code Description

H319 Causes serious eye irritation.

 Print date
 22/12/2023
 Production Name
 ULTRABOND ECO 380
 Page n.
 7 of 9

Code Hazard class and hazard category Description

3.3/2 Eye Irrit. 2 Eye irritation, Category 2

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)
BCF: Biological Concentration Factor
BEI: Biological Exposure Index
BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand COV: Volatile Organic Compound CSA: Chemical Safety Assessment CSR: Chemical Safety Report DMEL: Derived Minimal Effect Level

DMEL: Derived Millimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive
DSD: Dangerous Substances Directive
EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration

Print date 22/12/2023 Production Name ULTRABOND ECO 380 Page n. 8 of 9

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 5: Firefighting measures
- SECTION 6: Accidental release measures
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Print date 22/12/2023 Production Name ULTRABOND ECO 380 Page n. 9 of 9